

# Teclit® Alutape

Reinforced aluminium tape

**INSPIRED  
BY  
NATURE.**



## Product description

The reinforced aluminium tape ROCKWOOL Teclit Alutape is specially designed for taping joints in Teclit insulation. Thanks to its fibreglass reinforcement and strong polyacrylate adhesive strip, the tape is extremely resistant to tearing. Teclit Alutape is highly wear-resistant and its adhesive strength increases over time. This tape is therefore ideal for sealing insulation joints in the Teclit insulation system.

## Application

Taping joints and compartments in insulation material with an aluminium outer layer – especially cold insulation in the Teclit system: Teclit PS 200 and Teclit LM 200.  
Can also be used for any insulation work with products with an aluminium outer layer such as ROCKWOOL LM Klima (EF), ROCKWOOL Klimarock, ROCKWOOL 810, Conlit 150 U, Conlit Steelprotect Board Alu, Conlit PS EIS and Conlit Ductrock.

# Teclit Alutape

## Versterkte aluminium tape

### Product benefits

- Suitable for heat and cold insulation;
- High adhesive strength;
- Wear-resistant.

### Product range

Width (mm)	Length (m)	Rolls / pack
50	50	24
75	50	16
100	50	12

### Technical information

	Symbol	Value	Standard
Thickness		0.13 +/- 0.03	EN 1942*
Adhesive strength		≥ 6 N/cm	EN 1939*
Long-term temperature resistance		-40 °C to +80 °C	
Working temperature		+5 °C to +40 °C	
Water vapour diffusion resistance	μ	≥ 10,000	EN ISO 12572

\* In accordance with the current EN.

### Handling

For the processing guidelines for ROCKWOOL Teclit, we refer to the "ROCKWOOL Teclit Installation Manuel" brochure.



### Services

#### Technical advice

You can contact our specialists for advice on building regulations, thermal calculations, details, product applications, use and topical issues such as energy efficiency, fire safety, circularity and acoustics. Our technical specialists would be happy to consult with you at an early stage in order to find the optimal insulation solution for your project.

[rockwool.nl/technischadvies](https://rockwool.nl/technischadvies) · [rockwool.be/contact](https://rockwool.be/contact)

#### ROCKWOOL B.V.

Industrieweg 15, 6045 JG Roermond, The Netherlands  
Postbus 1160, 6040 KD Roermond, The Netherlands  
T 0475 35 35 35  
E [info@rockwool.nl](mailto:info@rockwool.nl) · [rockwool.nl](https://rockwool.nl)

#### ROCKWOOL Belgium NV

Oud Sluisstraat 5, 2110 Wijnegem, Belgium  
T 02 715 68 05  
F 02 715 68 76  
E [info@rockwool.be](mailto:info@rockwool.be) · [rockwool.be](https://rockwool.be)



We reserve the right to make product modifications without prior notice.  
ROCKWOOL cannot accept liability for any typographical or other errors or for any incomplete information.