

BTV SELF-REGULATING HEATING CABLE



nVent RAYCHEM BTV self-regulating trace heating cables provide freeze protection and process temperature maintenance, up to 150 °F/65 °C, of pipes/vessels without steam cleaning requirements. They withstand intermittent exposure to 185 °F/85 °C and are hazardous area approved. The polyolefin outer jacket (-CR) is suitable for mild inorganic solutions. The fluoropolymer outer jacket (-CT) provides high chemical resistance against aggressive organics and corrosives.

FEATURES

Simplified design in hazardous area: unconditional T6 class

Fast installation: cut-to-length, multiple overlaps allowed, meter markings, user-friendly connections kits

Safe and efficient in operation: no overheating, uniform pipe temperatures, energy saving technology

Reliable during long life: 10 year product warranty available, maintenance free

SPECIFICATIONS

Max Maintain or Continuous Exposure Temperature, Power On/Off:	65 °C
Max Intermittent Exposure Temperature, Power On/Off:	85 °C
Supply Voltage:	200 – 277 V
Ground Path Type:	Braid
Area Classification:	Non-Hazardous; Hazardous

Catalogusnummer	Naam van het item	Outer Jacket Material	Nominal Power Output @ 10°C, 230V
414809-000	5BTV2-CR	Modified Polyolefin	16 W/m
469145-000	3BTV2-CT	Fluoropolymeer	9 W/m
487509-000	5BTV2-CT	Fluoropolymeer	16 W/m
914279-000	3BTV2-CR	Modified Polyolefin	9 W/m
008633-000	8BTV2-CT	Fluoropolymeer	25 W/m
479821-000	8BTV2-CR	Modified Polyolefin	25 W/m
567513-000	10BTV2-CT	Fluoropolymeer	29 W/m
677245-000	10BTV2-CR	Modified Polyolefin	29 W/m

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Noord-Amerika

Tel +1.800.545.6258

Fax +1.800.527.5703

thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511

Fax +32.16.213.604

thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688

Fax +86.21.5426.3167

cn.thermal.info@nvent.com

Latijns-Amerika

Tel +1.713.868.4800

Fax +1.713.868.2333

thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER