

1	EU - TYPE EXAMINATION CERTIFICATE					
2	Equipment or Protective System Intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU					
3	EU - Type Examination Certificate Number:	Baseefa13ATEX01	37 Issue 6			
3.1	In accordance with Article 41 of Directive 2014/34/EU, EC-Type Examination Certificates referring to 94/9/EC that were is existence prior to the date of application of 2014/34/EU (20 April 2016) may be referenced as if they were issued in accordance with Directive 2014/34/EU. Supplementary Certificates to such EC-Type Examination Certificates, and new issues of succertificates, may continue to bear the original certificate number issued prior to 20 April 2016.					
4	Product:	ETS-05 Electronic	Thermostat			
5	Held by:	nVent Thermal Bel	gium NV			
6	Address:	Research Park Haa	srode - Zone 2, Rom	einse straat 14, B-3001	Leuven, Belgium	
7	This re-issued certificate extends EC Type Examination Certificate No. Baseefa13ATEX0137 to apply to product designed ar constructed in accordance with the specification set out in the Schedule of the said certificate but having any variation specified in the Schedule attached to this certificate and the documents therein referred to.				product designed and having any variations	
8	SGS Fimko Oy, Notified Body number 0598, in accordance with Article 17 of Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.					
8.1	The original certificate was issued by SGS Baseefa Ltd (UK Notified Body 1180). It, and any supplements previously issued by SGS Baseefa Ltd have been transferred to the supervision of SGS Fimko Oy (EU Notified Body 0598). The original certificate number is retained.				ents previously issued y 0598). The original	
	The examination and test results are re	corded in confidential	Report No. See Cert	ificate History		
9	Compliance with the Essential Health	and Safety Requireme	ents has been assured l	by compliance with:		
	EN IEC 60079-0:2018 EN IEC 60079-7:2015+A1:2018 EN 60079-11:2012 EN 60079-18: 2015 EN 60079-31				EN 60079-31:2013	
	except in respect of those requirements	s listed at item 18 of t	ne Schedule.			
10	If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.					
11	This EU - TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by this certificate.					
12	The marking of the product shall inclu	de the following:				
	🐼 See schedule					
	SGS Fimko Oy Customer Reference	No. 5034	Proje	ect File No. 20/0458		
This doo Condition advised	cument is issued by the Company subject to ons.aspx . Attention is drawn to the limitatio that information contained herein reflects	their General Condition. n of liability, indemnific the Company's finding	s for Certification Servic cation and jurisdiction is as at the time of their	es accessible at hiip://www sues defined therein. Any intervention only and with	w.sgs.com/en/Terms-and- holder of this document is hin the limits of Client's	

advised that information contained nerein reflects the Company's findings at the time of their intervention only and within the limits of Client's instructions, if any. It does not necessarily indicate that the equipment may be used in particular industries or circumstances. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, schedule included, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Fimko Oy Takomotie 8 FI-00380 Helsinki, Finland Telephone +358 (0)9 696 361 e-mail <u>sgs.fimko@sgs.com</u> web site <u>www.sgs.fi</u> Business ID 0978538-5 Member of the SGS Group (SGA SA)

Tuomas Hänninen SGS Fimko Oy



13 14

Certificate Number Baseefa13ATEX0137 – Issue 6

Schedule

15 Description of Product

The nVent ETS-05 Electronic Thermostat provides accurate temperature control for heating cables.

It comprises a plastic box with terminals inside for connection to the sensor and to the incoming user connections. Relay contacts are present to allow resistive loads of up to 230V a.c. at 32A to be controlled.

ETS-05-a1-bb-c

The supply range for the equipment is 99 to 121V a.c. Supply & relay terminal block TB1 $U_m = 253V$. Rated current = 32A. Relay terminal block TB3 (if present) $U_m = 253V$.

ETS-05-a1R-bb-c

The supply range for the equipment is 99 to 132V a.c. $U_m = 253V$. Supply & relay terminal block TB1 Um = 253V. Rated current = 32A. Relay terminal block TB3 (if present) Um = 253V.

ETS-05-a2-bb-c

The supply range for the equipment is 195 to 230V a.c. $U_m = 253V$. Supply & relay terminal block TB1 Um = 253V. Rated current = 32A. Relay terminal block TB3 (if present) Um = 253V.

ETS-05-a2R-bb-c

The supply range for the equipment is 195 to 277V a.c. $U_m = 277V$. Supply & relay terminal block TB1 Um = 277V. Rated current = 32A. Relay terminal block TB3 (if present) Um = 277V.

The options a bb & c affect the operational non-safety aspects:-

 $a = A (0^{\circ}C \text{ to } 49^{\circ}C \text{ model})$

H (0°C to 499°C model)

L (0°C to 199°C model)

bb = A (American market version)

= E (European market version)

- = J (Japanese market version)
- c = A (Alarm output model) Rated alarm output = 275V, 3A resistive.
 - = not present (Alarm output not present)

Sensor Connections - Terminal Block TB2

- $U_{\rm o} = 5.88 V$
- $I_{\rm o} = 29 {\rm mA}$
- $P_{\rm o} = 43 {\rm mW}$
- $C_i = 26 nF$
- $L_i = 0$
- $U_i = 0$

The capacitance and either the inductance or inductance to resistance ratio (L/R) of the load connected to hazardous area terminals must not exceed the following values:

GROUP	CAPACITANCE	INDUCTANCE (DR L/R RATIO
	(µF)	(mH)	(µH/ohm)
IIC	43	43	843
IIB	1000	172	3373
IIA	1000	345	6746



The above load parameters apply where:

1. The external circuit contains no combined lumped inductance L_i and capacitance C_i greater than 1% of the above values, or

2. The inductance and capacitance are distributed as in a cable, or

3. The external circuit contains either only lumped inductance or lumped capacitance

in combination with a cable.

In all other situations e.g. the external circuit contains combined lumped inductance and lumped capacitance, up to 50% of each of the L and C values is allowed.

The equipment is marked:

 \Box II 2(1)GEx eb ia mb [ia Ga] IIC T5 Gb $-40^{\circ}C \le Ta \le +60^{\circ}C$ \Box II 2DEx tb IIIC T100^{\circ}C Db

16 Report Number

See Certificate History.

17 Specific Conditions of Use

None

18 Essential Health and Safety Requirements

In addition to the Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9, the following are considered relevant to this product.

Clause	Subject	Compliance
1.2.7	LVD type requirements	Standards require manufacturer's declaration, supplied.
1.2.8	Overloading of equipment (protection relays, etc.)	Covered by installation rules and manufacturer's instructions
1.4.1	External effects	The Purchaser should make the manufacturer aware of such issues. Covered in Instructions
1.4.2	Aggressive substances, etc.	The Purchaser should make the manufacturer aware of such issues. Covered in Instructions

19 Drawings and Documents

New drawings submitted for this issue of certificate:

Number	Sheet	Issue	Date	Description	
RGD 1102-107	1	6	01/05/2021	ETS-05 nVent Certification Label	
This drawing is held with IECEx BAS 13.0071 Issue 6.					

Other applicable drawings are listed on Baseefa13ATEX0126 Issue 5.

20 Certificate History

Certificate No.	Date	Comments
Baseefa13ATEX0137	26 August 2014	The release of the prime certificate. The associated test and assessment against the requirements of EN60079-0: 2012, EN60079-7: 2007, EN60079-11: 2012, EN60079-18: 2009 & EN60079-31: 2013 is recorded in Report GB/BAS/ExTR14.0185/00 for Project 12/0565
Baseefa13ATEX0137 Issue 1	21 December 2016	This issue reflects the issue of Baseefa13ATEX0126 Issue 1. Report GB/BAS/ExTR16.0395/00, Project 16/0987

Certificate Number Baseefa13ATEX0137 Issue 6



Certificate No.	Date	Comments		
Baseefa13ATEX0137/2	28 February 2018	To permit the use of an alternative opto-coupler and the correction of the marking code. See report GB/BAS/ExTR18.0099/00 for project 17/0869.		
Baseefa13ATEX0137/3	22 January 2019	To confirm the certificate is now held in the name of nVent Thermal Belgium BV, and to permit the label to show name of nVent Thermal Belgium BV. See GB/BAS/ExTR18.0125/00 for project 17/0864.		
Baseefa13ATEX0137/4	8 April 2020	To permit the addition of a new variant model ETS-05-x3-x that has an increased voltage range of 195V to 277V, and an increased $U_{\rm m}$ of 277V. See report GB/BAS/ExTR20.0070/00 for project 20/0005.		
Baseefa13ATEX0137 Issue 5	10 August 2020	This issue of the certificate incorporates previously issued primary & supplementary certificates into one certificate, permits the use of an alternative enclosure, and confirms the equipment meets the requirements of EN IEC 60079-0:2018, EN IEC 60079-7: 2015+A1:2018 and EN 60079-18: 2015. See report GB/BAS/ExTR20.0119/00 for project 20/0123.		
Baseefa13ATEX0137 Issue 6	30 September 2021	This issue of the certificate permits the addition of models with alarm outputs and permits the introduction of a new model naming convention. See report GB/BAS/ExTR21.0172/00 for project 20/0458.		
For drawings applicable to each issue, see original of that issue.				