

## Declaration of Performance No. 0552-CPR-2013-022

Unique identification code of the product-type: HT/Armaflex S

Intended use/es: Thermal insulation of building equipment and

industrial installations (ThiBEII)

Manufacturer: Armacell Iberia S.L. c/ Can Magi n° 1

Poligono Industrial Riera d'Esclanya, E-17213 Esclanya (Begur), Spain

System/s of AVCP: 3

Harmonised standard: EN 14304:2009+A1:2013

**Notified body/ies:** NB 0919, NB 0751, NB 0432

Declared performance/s:

Essential characteristics	Performance		
Thermal resistance / Thermal conductivity	Tubes	$d_N = 10 - 32$	$\lambda_{40^{\circ}\text{C}} \le 0.042 \text{ W/(m * K)}$ $\lambda(\vartheta_{\text{m}}) = (36.92 + 0.125 \cdot \vartheta_{\text{m}} + 0.0008 \cdot (\vartheta_{\text{m}} - 30)^{2})) / 1000$
Reaction to fire	Tubes	$d_N = 10 - 32$	Е
Durability of thermal resistance against ageing/ degradation	Dimensional stability <sup>1)</sup> Minimum service temperature ST(-)-50 (= -50 °C)		
Durability of thermal resistance against high temperatures	Maximum service temperature ST(+)110 (=110°C)		
Durability of reaction to fire against ageing/ degradation	Durability characteristics <sup>2)</sup>		
Durability of reaction to fire against high temperature	Durability characteristics <sup>2)</sup>		
Water permeability	NPD		
Water vapour permeability/ Water vapour diffusion resistance	Tubes	$d_N = 10 - 32$	$\mu$ 4000 ( $\mu \ge 4000$ )
Rate of release of corrosive substances	Trace quantities of water-soluble chloride ions CL80 (≤80 ppm)		
Acoustic absorption index	NPD <sup>3)</sup>		
Release of dangerous substances to indoor environment	NPD <sup>3) 4)</sup>		

The thermal conductivity of flexible elastomeric foam does not change with time

This declaration of performance is made available in accordance with Article 7(3) of Regulation (EU) No 305/2011 on our homepage: <a href="http://www.armacell.com/DoP">http://www.armacell.com/DoP</a>

The fire performance of flexible elastomeric foam products does not change with time.

<sup>&</sup>lt;sup>3)</sup> European test methods are under development.

No Performance Determined (NPD)



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Georg, Eleftheriadis, Technical Marketing Manager EMEA Begur, 22.10.2018

[signature]