

# PYRO-SAFE DG-SC

Intumescent fire protection filler for indoor and outdoor use.

Subject to errors, typographical errors and modifications. The specified details reflect the state of the art / the effective standard at the time of printing (09/2014). Please let us know when you need information about the legal and technical requirements or the manufacturer's specification that apply to your specific case. © Copyright svt Unternehmensgruppe, Seevetal PYRO-SAFE is a registered trademark © of svt Unternehmensgruppe, Seevetal.



## Product description

### Fields of application

Universal applicable intumescent fire protection filler on water-based dispersion for indoor and outdoor use.

### Product features

Resistant to moisture and UV-light. Forms an insulating layer when exposed to fire.

### Reaction to fire classification

E according to DIN EN 13501-1

### Applicability certificate

Approved by Deutsches Institut für Bautechnik, Berlin (DIBt).

• ETA -13/0100

Other standards on request

Joints

Pipes

Cables

## Technical Data

---

### Handling

- The surface has to be dry, dust-free und free of grease
- The application is done by filling
- The consumption depends on the size of the opening

### Ordering information

310 ml cartridge

### Storage

Protect the product from frost!

Cool and dry (+5 °C up to +25 °C).

### Safety instructions

Please refer to our MSDS (safety data sheet).

### Technical Data

Colour	anthracite
Density (+ 20 °C)	1,300 kg/m <sup>3</sup> ± 10%
Viscosity (+ 20 °C)	paste-like
Foam coefficient	15 - 26.5
Foaming pressure	1.00 - 1.90 N/mm <sup>2</sup>
Processing temperature	+5 °C up to +25 °C