

ABSORPTION

ABSORBEL NOP – convoluted sound absorbing foam



ABSORBEL	Thickness	Weight
S20+10 NOP PU	30 mm	0,8 kg/m ²
20+30 NOP	50 mm	1 kg/m ²
S20+30 NOP	50 mm	1 kg/m ²
S30+40 NOP	70 mm	1,2 kg/m ²
20+50 NOP	70 mm	1,2 kg/m ²
S20+50 NOP	70 mm	1,2 kg/m ²
S = self-adhesive PU= PU protective layer		

Description	Absorbel Nop is an open cell polyurethane convoluted foam surface, optionally covered with a polyurethane protective layer (PU). Absorbel Nop has a grey color and is suitable for indoor use.
Characteristics	<ul style="list-style-type: none"> - High sound absorbing value - No skin irritation or dust formation during processing - Flame retardant in accordance with DIN 53438, MVSS 302 - Easy to cut with a (Stanley) knife or with a saw band - Resistant to aging, hydrolysis and temperatures from -50 to 100 °C
Application	Wherever noise absorption has to be applied, without danger of penetrating moisture, oil or suchlike; in those cases we advise the application of absorption foam with a film layer.
Processing	<p>Non-self-adhesive sheets should be bonded with TEROKAL-2444 contact adhesive (approx. 300 g/m²) Surface must be clean, dry and free from dust and grease. We recommend priming rough or porous surfaces (i.e. wood, stone) with TEROKAL-2444 Good adhesion is obtained by carefully pressing and rolling down Do not process sheets at temperatures below 10 °C For further instructions see also the application sheet of self-adhesive products</p>
Dimensions	<p>Sheets of 1000 x 1400 mm For weights and thickness see table above Die-cut tailor-made parts available</p>

DISCLAIMER
De omschreven toepassingen en aanbevelingen zijn zo correct mogelijk weergegeven maar zijn vrijblijvend en bieden geen garanties. Bij twijfel over toepassing of verwerking zelf een test uitvoeren of contact met ons opnemen. We behouden ons het recht om zonder kennisgeving vooraf, productgegevens te wijzigen.

ABSORPTION VALUE

Absorption material
Measured follows

ABSORBEL NOP
DIN 52215

