

# T-25-FDF3 WELDFASTENERS



## General description

The FDF3 weldfasteners consist of a steel shank firmly crimped on a steel washer head. The FDF3 weldfasteners allow the fixing of insulation material on sheet metal such as airducts, metal beams, metal industrial equipment, etc. in a single operation.



It is recommended to use our welding equipment CDW-72 or FDD-31.


## Recommended use

Our FDF3 weldfasteners are suitable for plain insulation (without aluminium facing).

## Technical specification

SHANK	Material	galvanized steel
	Diameter	3,5 mm (10 ga.)
	Lengths	10 to 51 mm (3/8" to 2")
HEAD WASHER	Material	galvanized steel
	Diameter	30 mm (1-3/16")
	Thickness	0,4 mm (28 ga.)
	Edges	bevelled

## Application




Fix earth clamp of the welder to the sheet metal.

Lay insulation on sheet metal




Place the weldfastener FDF3 on the magnetic head of the gun.

Adjust the voltage according to the type and thickness of sheet metal



Press the pin through the insulation until the point meets the sheet metal and press the trigger



Information contained herein is based on careful tests and experience. It reflects our knowledge and is for guidance purpose only. It is given in good faith and user should ensure that the product is fit for purpose before any application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Manufacturer and distributor are not responsible for any non-recommended use or consequential damage.

2016.06.06