

DECLARATION OF PERFORMANCE Date of issue: 10/18/2016 Replaces: No --- - CPR --/--- - yyyy/# of: dd/mm/yyyy No. 0761-CPR-16/0309-2016/10 PROMASEAL®-AG Unique identification of the product-type: Type and batch numbers: as given on the packaging of the product Intended uses as given in the ETA-16/0309: 3.1 - PROMASEAL®-AG is an intumescent fire stopping mastic for non-combustible pipes (with non-combustible insulation), combustible pipes, as well as for cables, cable bundles and cable conduits in penetrations in walls and floors. 3.2 - The product is intended for: - use at internal conditions with humidity < 85% RH, excluding temperatures below 0°C, without exposure to rain and UV (TR 024:2009, type Z2) - use at internal conditions with humidity ≥ 85%, excluding temperatures below 0°C, without exposure to rain and UV (TR 024:2009, type Z1); - use at temperatures below 0°C, but no exposure to rain or UV (TR 024:2009, type Y2); - use at temperatures below 0°C, with exposure to UV but no exposure to rain (TR 024:2009, type Y1); Name and contact address of the manufacturer: Promat International NV Bormstraat 24 B-2380 Tisselt Belgium Plant:12 www.promat-international.com Authorised representative: not applicable. System or systems of Assessment and Verification of Constancy of Performance (AVCP): see table under section 9. The construction product is not covered by a harmonised standard (hEN). The declaration of performance concerns a construction product for which a European Technical Assessment has been issued. The Österreichische Institut für Bautechnik (OIB, Austria) has issued an ETA for this product with no. ETA-16/0309 based on ETAG 026-1 and ETAG 026-2. Notified product certification body: No. 0761 (MPA Braunschweig) Certificate of Constancy of Performance 0761 - CPR - 0546 **Declared performance Essential characteristics** AVCP systems Performance Harmonised technical specification BR1: Mechanical resistance and stability. BR2: Safety in the case of fire: Reaction to fire: This characteristic depends on the tested Resistance to fire: 1 assembly. A fire resistant construction, in which the ETA 16/0309 product was used, has been tested and the performance class has been established in a classification document in accordance with the applicable part of EN 13501. BR3: Hygiene, Health and the Environment: Air permeability: NPD (No Performance Declared) Water impermeability: NPD (No Performance Declared) Release of dangerous substances: Declaration (filed with the Technical ETA 16/0309 Approval Body) BR4: Safety and accessibility in use: NPD (No Performance Declared) Mechanical resistance and stability: Resistance to impact and movement: NPD (No Performance Declared) ETA 16/0309



id dollbo

Adhesion:		NPD (No Performance Declared)	
BR5: Protection against noise:		<u> </u>	
Airborne sound insulation:		NPD (No Performance Declared)	ETA 16/0309
BR6: Energy Economy and Heat Retenti	on:	<u> </u>	
Thermal conductivity:	-	NPD (No Performance Declared)	
Water vapour permeability (transmission coefficient):	-	NPD (No Performance Declared)	ETA 16/0309
Durability:		·	
Basic durability assessment:		In accordance with the declared use, class Z2, Z1, Y2, Y1 according EOTA TR024 and in conformity with ETAG 026-2.	ETA 16/0309

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

The reader of this document is invited to verify on the website www.promat-ce.eu the relevant version..

The Safety Data Sheet (SDS) 1907/2006/EG for PROMASEAL®-AG is available on request.

Signed for and on behalf of the manufacturer by:

Name: Bettina Rothböck

Function: Product Manager Fire Stopping & Intumescent

Seals

Linz, 10/18/2016 Signature: